

Summary Information

Property Reference: 4908-0001-1008a

Issued on Date: 05.Jul.2012

Survey Reference: 1008a

Prop Type Ref:

Property: Apartment 4 The Watchmakers, 22, Lord Street, COVENTRY, CV5 8DA,

SAP Rating: 79 C **CO2 Emissions (t/year):** 1.24 **DER:** 0.00 Pass **Reduction:** 0.0% **FEE:** 65.9 **ZC8:** 0.00
Environmental: 83 B **General Requirements Compliance:** Fail **TER:** 0.00 **HLP:** 1.61 **Energy cost:** £ 352

CfSH Results **Version:** **ENE1 Credits:** N/A **ENE2 Credits:** N/A **ENE7 Credits:** N/A **CfSH Level:** N/A

Surveyor: Alison Cleaver, Tel: 01858434392

Address: Overfield Avenue, Market Harborough, Leics, LE16 7LS

Client:

Software Version: Elmhurst Energy Systems SAP2009 Calculator (Design System) version 3.06r13

SAP version: SAP 2009, Regs Region: England and Wales (Part L1A 2010), Calculation Type: Conversion - new dwelling

SUMMARY FOR INPUT DATA FOR Conversion - new dwelling

Page 1 of 4

1.0 Property Type Flat, End-Terrace
 2.0 Number of Storeys 1
 3.0 Date Built 2011
 3.0 Property Age Band
 4.0 Sheltered Sides 2
 5.0 Sunlight/Shade Average or unknown
 6.0 Measurements

	Internal Perimeter	Internal Floor Area	Average Storey Height
Ground Floor:	18.9	55.63	2.4

7.0 Living Area 20.7

8.0 Thermal Mass Parameter Simple calculation

9.0 External Walls		U-Value	Element	Kappa	Gross Area	Nett Area
Description	Construction					
External Wall 1	Other	0.34		0.00	47.25	32.31

9.1 Party walls		Element	Kappa	Area
Description	Construction			
Part	Steel frame		20.00	21.55
Party wall 2	Other		0.00	6.25

10.1 Party Ceilings		Element	Kappa	Area
Description	Construction			
Party Ceiling 1	Concrete floor slab, carpeted		100	55.63

11.1 Party Floors		Element	Kappa	Area
Description	Construction			
Party Floor 1	Concrete floor slab, carpeted		100	55.63

12.0 Opening Types		Type	Glazing	Glazing Gap	Argon Filled	Solar Trans	Frame Type	Frame Factor	U value
Description	Data Source								
Opening Type 2	SAP table	Window	Secondary Glazing			0.76	Wood	0.70	2.40

13.0 Openings		Location	Orientation	Curtain Type	Overhang Ratio	Wide Overhang	Width	Height	Count	Area	Curtain Closed
Name	Opening Type										
Opening 2	Window - Opening Type 2	External Wall 1	East	None	0	No	0	0	0	8.64	0
Opening 4	Window - Opening Type 2	External Wall 1	West	None	0	No	0	0	0	6.30	0

14.0 Conservatory None
 15.0 Draught Proofing 100
 16.0 Draught Lobby Yes
 17.0 Thermal Bridging Default
 Y-value 0.15
 Description
 18.0 Pressure Testing No
 Designed q50 15.00

Property Tested ?
 As Built q50
 Same As Designed ?

19.0 Mechanical Ventilation				
Mechanical Ventilation System	No			
Present				
Approved Installation				
Windows open in hot weather	Windows fully open			
Cross ventilation possible	Yes			
Night Ventilation	No			
Air change rate	6.00			
Mechanical Ventilation data Type				
Type				
MV Reference Number				
Configuration				
MVHR Duct Insulated				
Manufacturer SFP				
Duct Type				
MVHR Efficiency				
Wet Rooms				
Brand, Model				
20.0 Fans, Open Fireplaces, Flues				
	MHS	SHS	Other	Total
Number of Chimneys	0		0	0
Number of open flues	0		0	0
Number of intermittent fans				2
Number of passive vents				0
Number of flueless gas fires				0
21.0 Cooling System				
	No			
22.0 Lighting				
Internal				
Total number of light fittings	6			
Total number of L.E.L. fittings	5			
Percentage of L.E.L. fittings	83.33			
External				
External lights fitted	No			
Light and motion sensors				
23.0 Electricity Tariff				
	Standard			
24.0 Heating Systems				
Main Heating 1	Database			
Description	heating 1			
Percentage of Heat	100.00			
Main Heating 2	None			
Description				
Percentage of Heat				
Community Heating				
Secondary Heating				
Water Heating	Main Heating 1			
Flue Gas Heat Recovery System	No			
Waste Water Heat Recovery System	No			
1				
Waste Water Heat Recovery System	No			
2				
Solar Panel	No			
25.0 Main Heating 1				
Database Ref. No.	15701			
Fuel Type	Mains gas			
Main Heating	BGW			
TestMethod				
SAP Code	104			
Efficiency (Split Efficiencies) %				
Efficiency (Split Efficiencies) %				
In Winter	89.9			
In Summer	79.8			
Model Name				
Manufacturer				
Controls	CBG			
Delayed Start Stat	Yes			
Sap Code	2108			
Burner Control				
Boiler Compensator	None			
HETAS approved System				
Oil Pump Inside				
FI Case				
FI Water				
Flue Type	Balanced			
Smoke Control Area				
Fan Assisted Flue	Yes			

Is MHS Pumped	Pump in heated space
Heat Emitter	Radiators
Underfloor Heating	
Electric CPSU Temperature	
Combi boiler type	Standard Combi
Combi keep hot type	None
Combi store type	
<hr/>	
27.0 Community Heating	
Space Community Heating	
Distribution Loss	
Distribution Loss Value	
Controls	
SAP Code	
Water Community Heating	
Distribution Loss	
Distribution Loss Value	
Charging Linked To Heat Use	
<hr/>	
28.0 Secondary Heating	
Description	
SHS efficiency %	
SAP Code	
HETAS Approved System	
Smoke Control Area	
Test Method	
Manufacturer	
Model Name	
<hr/>	
29.0 Water Heating	
Water use <= 125 litres/person/day	HWP
SAP Code	Yes
SAP Code	901
Immersion Heater	
Summer Immersion	
Supplementary Immersion	
Immersion Only Heating Hot Water	
29.1 Flue Gas Heat Recovery System	
Database ID	
Brand Model	
Details	
29.2 Waste Water Heat Recovery System	
Total rooms with shower and/or bath	
30.0 Hot Water Cylinder	
Cylinder Stat	None
Cylinder In Heated Space	
Independent Time Control	
Insulation Type	
Insulation Thickness	
Cylinder Volume	
Loss (kwh/day)	
Pipes insulation	
In Airing Cupboard	
<hr/>	
31.0 Solar Panel	
Solar Panel Area	
Area Type	
Panel Type	
n0, a1, A/G ratio	
Orientation	
Elevation	
Overshading	
Solar Storage Volume	
Pump electrically powered	
Combined Cylinder	
<hr/>	
32.0 Thermal Store	
Thermal Store Pipework	None
	within a single casing
33.0 Photovoltaic Unit	
Apportioned KWh/Year	
34.0 Wind Turbines	
Terrain Type	Urban
Wind Turbines	
Count	
Apportioned Kwh/year	
Rotor Diameter	
Hub Height	
35.0 Small-scale Hydro	
Electricity Generated	
Description	
Apportioned kWh/Year	
<hr/>	
Recommendations	
None	

Further measures to achieve even higher standards

None